



# Dehumidifier KT-23

## Dehumidifier

This powerful and quiet dehumidifier has a polished design explicitly realized for residential use, in places such as basement rooms, offices, cellars, garages, small archives, etc. High quality product, it is characterized by an elegant appearance and a refined planning of the refrigerating section which guarantees high performances in every use condition and with low consumption. The **KT-23** dehumidifier has an electric card which manages the defrosting periods when it works in a low temperature location and prevents compressor close starts. The air filter guarantees an efficient protection of the refrigeration section from dust. The device possibly has a direct condensation drain tube. The mechanical humidistat enables to modify the desired humidity level with a graduated scale. The dehumidifier is geared with castors to ease the moves. Autorestart on board for automatic restarting in case of sudden default of power source.



## Technical data

Voltage	230/1/50 V/ph/Hz
Rated condensation capacity (at 32°C, 90% R.H.)	19 l/24h
Related average power consumption	178 W
Air flow (with clean filter)	250 m3/h
Condensed water tank capacity	5,5 lt
Refrigerant	R134a
Functioning temperature range	+12/+35 °C
Functioning relative humidity range	35-99 %
Dimensions LxDxH	350 x 320 x 700 mm
Weight	21 Kg
Sound pressure level (at 3 mts in free field)	39 Db(A)